

CNC-92E16D0T-IRF HD 1080p IR Bullet Camera



Key Features

- 2 megapixel high performance CMOS
- Analog HD output, up to 1080p resolution
- Day/Night switch
- Smart IR
- Up to 20 m IR distance
- Switchable TVI/AHD/CVI/CVBS
- IP66

Specifications

| Camera | |
|----------------------|---|
| Image Sensor | 2MP CMOS image sensor |
| Signal System | PAL/NTSC |
| Effective Pixels | 1920 (H) × 1080 (V) |
| Min. illumination | 0.01 Lux@(F1.2,AGC ON), 0 Lux with IR |
| Shutter Time | 1/25 (1/30) s to 1/50,000 s |
| Lens | 2.8 mm, 3.6 mm, 6 mm optional |
| | Field of view: 103° (2.8 mm), 82.2° (3.6 mm), 54° (6 mm) |
| Lens Mount | M12 |
| Day & Night | ICR |
| Angle Adjustment | Pan: 0° to 360°, Tilt: 0° to 180°, Rotation: 0° to 360° |
| Synchronization | Internal synchronization |
| Video Frame Rate | 1080p@25fps/1080p@30fps |
| HD Video Output | 1 analog HD output |
| S/N Ratio | >62 dB |
| General | |
| Operating Conditions | -40 °C to 60 °C (-40 °F to 140 °F), Humidity 90% or less (non-condensation) |
| Power Supply | 12 V DC ± 15% |
| Power Consumption | Max. 4 W |
| Protection Level | IP66 |
| IR Range | Up to 20 m |
| Dimensions | Φ 70 mm × 154.5 mm (Φ 2.76" × 6.08") |
| Weight | 400 g (0.88 lb.) |